D A T A S H E E T



LOW COST, LOW MAINTENANCE, EASY TO USE, 16-CAMERA DVR

The Eco16 is a low cost, compact digital video recorder designed to replace the traditional VCR/multiplexer combination bringing all the benefits of digital security monitoring to the cost conscious user.

The Eco16 is designed to have the "look and feel" of a traditional CCTV system, however the user need never worry about rewinding, changing or replacing tapes as they wear out. When the available hard disk space is full, Eco16 automatically begins recording over the oldest video. Any periods of recorded video can be manually protected to prevent them from being overwritten.

The elimination of tape management issues and VCR maintenance costs means that Eco16 literally provides a fit and forget solution, with quick and easy access to recorded images if and when video needs to be reviewed.

Medium size organizations can benefit from Eco16's ability to copy incidents to CD-R. All hard disk recordings and images copied to CD provide tamper proof mechanisms approved for evidence.

Playback of images from the CD is via a standard CD-ROM drive. The CD playback software will simply "auto-run" and does not require the installation of software on the users PC.

Among the many features also included as standard on Eco16 are multiway display, picture in picture viewing, password protected access, a secondary spot monitor, out of hours remote monitoring using free network viewing software, and Dedicated Micros trade mark plug and play set-up with user-friendly interface to keep installation and operator training to a minimum.

For further information, please visit the website: www.dedicatedmicrosus.com or contact customer services at (800) 864-7539.

NetVu Connected

- Low cost entry level digital solution for small business applications
- Quick and easy to install
- Integrated CD-R (CD writer)
- No VCR Tapes or maintenance
- Second live deterrent spot monitor output
- Simultaneous record, playback, background image archiving, remote viewing and playback with no loss of performance
- Recording of up to 30pps (NTSC) 25pps (PAL)
- Full remote control and observation over local Ethernet, Broadband Internet or dial up Modem connection
- Multiscreen, quad display and picture in picture viewing
- Built in Activity Detection
- Controlled via NetVu ObserVer over the network



SPECIFICATION

LANGUAGESEnglish, French, German, Spanish, Italian, Chinese, Russian, Czech, Polish, Dutch, Hungarian, Swedish and Croatian.

HIDDEN CAMERAS
Option to view all or selected cameras, without affecting cameras recording.

MONITOR VIEWING

Main monitor:
Full screen, programmable sequence.
Programmable picture-in-picture, quad.
x2 electronic zoom on live images, freeze frame.
Mon A: Composite video BNC connector.
Spot monitor:
Full screen, programmable sequence.
Mon B: Composite video BNC connector.

SCHEDULING
Choice of day, night or weekend offers the ability to automatically:
Switch activity on/off
Alter the record rate for standard, alarm and activity recording
Activation is via timer

ACTIVITY DETECTION
Programmable 16 x 16 masking grid for each camera view.
5 levels of sensitivity.
Options:
Trigger light duty relay output 500mA @ 20V max

- ALARMS

 1 normally open global alarm contact available via back panel.

 16 normally open/closed camera specific alarm contacts via back panel.

 Main monitor display of last alarm, 2 second dwell per alarmed camera, return to pre-alarm display

 Trigger light duty relay output 500mA @ 20V max

SEARCH AND PLAYBACK

- One touch playback
 Frame advance/rewind, fast picture search and pause keys
 Event list, including event list filter with unique quadrant preview facility
 GOTO time and date
 Playback in quad, picture in picture and full screen

RECORDINGPlayback and record to hard disk simultaneously

Hard disk sizes are rapidly increasing in capacity. Please contact customer services or DM web site, for latest available disk capacity for Eco16.

Protected images:
The end user can manually configure sections of recorded images to be permanently protected from overwrite. The system can also be configured to protect images automatically when the global alarm is activated.

RECORD RATEMaximum record rate up to 30pps (NTSC) and 25pps (PAL)

TIMED EXPIRY

Timed expiry option allows images to be held for a selected number of days
 Images on the disk, which are older than the number of days, selected are not accessed

EVENT COPYING

Event sequences and user defined recorded sequences can be saved to the internal CD-R drive of Eco16.

The sequences of images are digitally signed for authentication purposes. Playback of images from the CD is via a standard CD ROM drive. The CD playback software will auto-run and does not require the installation of software on the users PC.

DIGITAL SIGNATURE

The use of digital signatures makes it possible to detect whether single image or a sequence of images have been tampered with.

ECO16 NETWORKING CAPABILITIES

Standard Ethernet connection provides live and recorded viewing on a networked PC using DM's NetVu ObserVer or web pages using Internet Explorer. Network viewing is independent and does not affect the recording or local operation. The amount of bandwidth the Eco16 uses on the network can be adjusted by the bandwidth limitation option.

- Network ObserVer software features include:
 Live full, quad or multiway format screens
 Fast forward and rewind, playback and frame advance/rew
 GOTO time and date and unique quadrant event review
 File export over the network
 Copy single images as IPEG and sequences of images to save to PC
 Configurable password protection
 Replay server feature removes the need for additional viewing software when video is downloaded to a PC

- Web pages features include:
 Viewing of live images in single, quad or multiway format
 Playback in single, quad or multiway format including GOTO function
 Password authentication
 System configuration via web pages

COLOR RESOLUTION

COMPRESSIONJPEG format files. 2CIF, CIF and QCIF compression.
User definable file compression size.

ECO16 DATA RS-232 serial port. 485-Bus support for IR interface. 1x Ethernet RJ-45 10/100Base-T connection.

CD-RWBuilt-in slim-line CD Writer for Compact Disk Recordable Media.

TEMPERATURE RANGE Occasions temperature 41-113 °F (5 – 40°C).

RELATIVE HUMIDITY 5% - 85% Non-condensing

2 5/8"(H) x 17 5/16" (W) x 16 1/8" (D) 66mm (H) x 440mm (W) x 409mm (D).

WEIGHT DVR

13lbs (5.9Kg) without PSU 14.5lbs (6.6Kg) with PSU.

POWER SUPPLY

Input Voltage: 100 – 230 VAC 50/60 Hz. Output Voltage: 5, +12, -12 VDC.

BUILT-IN CD WRITER RANGE	
DESCRIPTION	SHORT CODE
16 CAMERA COLOR DUPLEX WITH CDR 30PPS 160GB	ECO16 CD - 160GB
16 CAMERA COLOR DUPLEX WITH CDR 30PPS 300GB	ECO16 CD - 300GB

PLEASE CHECK THE WEBSITE FOR DETAILS OF COMPATIBLE PRODUCTS AND OTHER LATEST DEVELOPMENTS

FOR FURTHER INFORMATION PLEASE CONTACT

14434 Albemarle Point Place, Suite 100, Chantilly, Virginia 20151 USA Toll Free: 800 864 7539
Tel: +1 703 904-7738 Fax: +1 703 904-7743 and 23456 Hawthorne Blvd. Suite 100, Torrance, CA 90505, Tel +1 310 791-8666 Fax: +1 310 791-9877.
11 Oak Street, Swinton, Manchester M27 4FL UK Tel: +44 (0) 845 600 9500 Fax: +44 (0) 161 727 3300.

9-13 rue du Moulinet, 75013 Paris, France Tel: +33 1 45 81 99 99, Fax: +33 1 45 81 99 89.

16 New Industrial Road, #03-03 Hudson Techno Centre, Singapore 536204 Tel: +65 62858982 Fax: +65 62858646.

5/3 Packard Avenue, Castle Hill, NSW 2154, Australia Tel: +612 9634 4211 Fax: +612 9634 4811.

UB 2, San Gwann Ind. Est., San Gwann, Malta Tel: +356 21483 673 Fax: +356 21449 170.

Building 12, Suite 302, P.O.Box 500291, Dubai Internet City, Dubai, United Arab Emirates

Tel: +971 (4) 390 1015, Fax: +971 (4) 390 8655.

Delavska cesta 24, 4208 Sencur, Slovenia Tel: +386 4 279 18 90 Fax: +386 4 279 18 91.

Joseph Chantraineplantsoen 1, 3070 Kortenberg, Belgium Tel: +32 2751 3480 Fax: +32 2751 3481.



c(UL)us

