

speco technologies®

The Intensifier Series Bullet Camera



Includes
EZ Mount
Plate

HT-INTB8

Features

See In The Dark Without IR LEDs

- 560 lines of resolution
- 2.8-12mm DC auto iris varifocal lens
- Minimum illumination 0.002 lux (Intensifier @ 128x)
- Dual voltage 12VDC & 24VAC operation
- Full OSD operation
- SLC - Speco Light Compensation
- S/N Ratio more than 50dB (weight on)
- Weatherproof operation
- EZ mount system simplifies installation

Specifications

Image Pick-Up Device	1/3" Sony Super-HAD* CCD - 410K
Resolution	560 TV line
Minimum Illumination	0.002 lux - Intensifier @ 128X
S/N Ratio	More than 50dB (weight on)
White Balance	ATW/AWC/MANUAL (1800K - 10,500K)
Video Output	Composite video 1.0 Vp-p into 75 Ohm + test connection
Electronic Shutter	Auto/Manual (1/60 - 1/120,000 seconds)
OSD	Built-in - controlled by internal buttons
SLC (Speco Light Compensation)	Low, middle, High, Off, Selectable
Auto Gain	Low, middle, High, Off, Selectable
Reduce Noise	Low, middle, High, Off, Selectable
Day & Night (Color)	On / Auto Selectable
Sharpness	On / Off (Level Adjustable)
Privacy	On / Off (4 Programmable Zones)
Power Supply	24 Volts AC, 12 Volts DC - Dual Voltage
Power Consumption	210mA
Lens	DC Auto Iris Varifocal Lens (2.8mm-12mm)
Total Pixels	811(H) x 508(V)
Effective Pixels	768(H) x 494(V)
Scanning Frequency	15.734kHz(H) / 59.94Hz(V)
Scanning System	2:1 Interlace
Synchronization	Internal / Line lock in 24V AC
Operating Temperature	-14°F to 122°F - RH 95% Max.
Storage Temperature	-40°F to 140°F - RH 95% Max.
TV System	NTSC
Dimensions	3.94" W x 4.92" H x 8.19" L
Weight	3 lb.

*Super-Had is a trademark of The Sony Corporation

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880